

Club 40 Rules for the Airplanes- (Version 12-24-2009) **www.Club40Racing.com**

Airframes

The World Models Sky Raider Mach II ARF or ARC, per instructions

The World Models LA Racer 40 ARF per instructions.

The Sanaloma Laser, Inc, Club 40 Raider Kit, use WM hardware or allowed substitutes.

You may modify the cheek/nose area of the kit and older Sky Raiders to match the current WM product. Do not enclose.

Do not pinch narrower than the narrowest of current or previous airframes from WM

Airframe Regulations

Assemble according to the manual, with the materials provided, except for:

Recovering plane is allowed

No airframe modifications other than repairs or reinforcement.

Standard size servos or mini servos with 4 screws are required.

Dual aileron servos are allowed.

Minimum weight, without fuel, is 4 lb. and 8 oz., 4 lb. and 4 oz. for Sport class.

Control surfaces may be hinged with the supplied metal or CA hinges, other CA hinges, plastic hinges or hinge points (Robart or similar).

A minimum of 3 hinges per aileron, 4 per elevator and 3 per rudder are required.

Hinge lines may be sealed using tape, stick-on plastic covering, or iron-on plastic covering.

If wheels are substituted, must be as large in diameter and as wide as original

Must have canopy, original or very similar.

Do not remove any wood except to clear for Sport muffler or move throttle servo to the side.

Propulsion System Regulations

All engines must be stock, with stock carburetor, and muffler with original baffle, if any.

Shimming the engine mount to change the thrust line is acceptable.

Advanced Class Engines

Recommended: Thunder Tiger Pro .40 BB ABC w/Muffler

Acceptable Alternatives: SuperTigre GS-40, GMS .40 ABC BB, Evolution .40NT and OS .40 BB Sport Engines

Sport/Novice Class Engines

Thunder Tiger GP-42, OS .46 LA, OS .40 LA, OS .40 FP, Magnum .40 GP, TT .40 GP, Tower Hobbies 40.

Prop / Spinner:

1. Any spinner of not more than 2.5 inches in diameter is allowed.

2. Spinner weights that fit inside a spinner, Heavy hub and aluminum Safety Spinner nuts are allowed.

Any size of prop may be used.

Props shall be unmodified and commercially available. Balancing only will be allowed as defined in Section 7.5 of AMA Pylon Regulations or RCPRO Club 40 Rules.

Fuel tank:

Any brand of tank may be used.

Tanks may be raised or lowered to allow for consistent engine runs.

The tank may only be pressurized with muffler pressure.

Bubble less tanks that have an internal bladder may be used.

The stock tank may be converted to use a fuel bladder.

Hardware:

Control horns, push rods and linkages may be replaced with similar hardware.

Pushrods, if replaced, must exit the fuselage sides in the same position as original specification.

No EZ-type connectors on ailerons, elevator or rudder. They are only allowed on throttle. Also see section 8, especially a. and I, of AMA Pylon Regulations or RCPRO Club 40 Rules.

Battery packs may be four or five cell (or 2-3 cell LiPo) with a suggested minimum of 500 MaH.

Nylon wing bolts are allowed.

You may substitute machine screws, nuts and screws of same or larger diameter (#4 SAE is fine)

Race CD will have the final say on legality of "modified" aircraft.

Inspectors may use templates or a "standard" aircraft. See Technical Inspection Form

Any modification deemed to be an attempt to provide for speed enhancement, shall not be allowed.